


## COOL AND WARM WATER FEEDER

**Patent number:** JP7185521  
**Publication date:** 1995-07-25  
**Inventor:** ISHIKAWA TAKASHI  
**Applicant:** KOYO ISHIKAWA  
**Classification:**  
- **International:** C02F1/02; C02F1/20  
- **European:**  
**Application number:** JP19930334763 19931228  
**Priority number(s):**

### Abstract of JP7185521

**PURPOSE:** To effectively obtain safe and good water by arranging a hot water tank and a cool water tank back to back, providing the hot water tank with an aerating means to make hot water into soft water before transferring it to the cool water tank by a pumping means before using it.

**CONSTITUTION:** When water is used, city water is fed to a hot water tank 10 with a cover 30 opened. Next, by turning on the switch of a nichrome wire heater 11 to heat water at about 120 deg.C for 10min, bacteria and viruses are exterminated, and also odor is removed. Then, by driving a fan to jet bubbles BU from the lower end of a blowing pipe 36 and aerating the hot water, it is cooled to about 80 deg.C. By this aeration, the city water is made soft water, and also chlorine is removed. Then, a pumping means D is operated and the hot water is filtered by an active carbon plate 21 to transfer it to a cool water tank 20, and cooled by a cooling plate 2 to obtain cool water. The cool water is drawn out by a discharge pump 22 and used. When the level of the cool water attains to the lower limit LL, the pumping means D is restarted to replenish the hot water.



Data supplied from the esp@cenet database - Patent Abstracts of Japan

Best Available Copy

(19) 日本国特許庁 (J P)

(12) 公 開 特 許 公 報 (A)

(11) 特許出願公開番号

特開平7-185521

(43) 公開日 平成 7 年 (1995) 7 月 25 日

(51) Int.Cl. <sup>6</sup>	識別記号	庁内整理番号	F I	技術表示箇所
C 0 2 F 1/02	C			
1/20	A			

審査請求 未請求 請求項の数 1 O L (全 4 頁)

(21) 出願番号 特願平5-334763

(22) 出願日 平成 5 年 (1993) 12 月 28 日

(71) 出願人 592224389

石川 高陽

千葉県東金市田間745

(72) 発明者 石川 丘

千葉県東金市田間2201


(74) 代理人 弁理士 高橋 敏忠 (外 1 名)

(54) 【発明の名称】 冷温水供給装置

(57) 【要約】

【目的】 細菌やビールスを除去する。

【構成】 熱湯槽 10 に給水した水道水を、ニクロム線ヒータ 11 で加熱し細菌やビールスをも死滅させたのち、曝気手段 C からの気泡 B U で曝気することにより熱湯をうる。そして、ポンプ手段で冷水槽 20 に移送し冷却板 2 で冷却して冷水を得る。



Best Available Copy

